



Product Data Sheet

GSE CE Series Nonwoven Needleponched Geotextiles

Description

GSE "CE" Series geotextiles are staple fiber polypropylene nonwoven needleponched geotextiles developed and manufactured with the specific intent to meet AASHTO M288 requirements. These products are manufactured under a stringent quality management system which ensures that the product meets or exceeds the following specifications. They may also be produced with customized properties to meet the specific needs of customers and project requirements. GSE quality control laboratories are GAI LAP approved to provide a high level of confidence in the quality control data.

Specifications

Product Name		CE 4	CE 6	CE 8
Product Code				
(12.5' x 360') 500 sy		CE4N	CE6N	CE8N
(15' x 360') 600 sy		CE4	CE6	CE8
TESTED PROPERTY	TEST METHOD	MINIMUM AVERAGE ROLL VALUE		
Grab Tensile Strength, lb (N)	ASTM D 4632	112 (500)	157 (700)	200 (900)
Grab Elongation, %	ASTM D 4632	> 50	> 50	> 50
Puncture Strength, lb (N)	ASTM D 4833	40 (180)	56 (250)	79 (350)
Trapezoidal Tear, lb (N)	ASTM D 4533	40 (180)	56 (250)	78 (350)
UV Resistance (% retained after 500 hours)	ASTM D 4355	70	70	70
Apparent Opening Size, Sieve No. (mm)	ASTM D 4751	Site-specific	Site-specific	Site-specific
Permittivity, sec ⁻¹	ASTM D 4491	Site-specific	Site-specific	Site-specific
AASHTO M288 Class		3	2	1

NOTES:

- Note 1 – All values are minimum average roll values except apparent opening size in mm which is a maximum average roll value.
- Note 2 – All values in weaker principal direction.
- Note 3 – Roll lengths and widths have a tolerance of plus or minus 1%.

Applications

- Unpaved Roads and Industrial Yards
- Paved Roads and Parking Lots
- Subsurface Drains
- Erosion Control
- Recreational Facilities
- Waste Handling Systems
- Landscaping

Standard

Meets AASHTO M288 Requirements

Availability

These CE products are available immediately from your GSE sales representative or distributor

DS032 CE Series 10/26/06

This information is provided for reference purposes only and is not intended as a warranty or guarantee. GSE assumes no liability in connection with the use of this information. Please check with GSE for current, standard minimum quality assurance procedures and specifications.

GSE and other trademarks in this document are registered trademarks of GSE Lining Technology, Inc. in the United States and certain foreign countries.

North America	GSE Lining Technology, Inc.	Houston, Texas Havre de Grace, Maryland	800 435 2008	281 443 8564 443 730 0367	Fax: 281 230 8650 Fax: 410 939 1360
----------------------	-----------------------------	--	--------------	------------------------------	--